

longer required. And, since the performance of the 7250xi and 7250i is continuous throughout the range, the time consuming task of controlling to atmosphere and switching ranges is eliminated.

The 7250xi and 7250i not only provide unequalled precision, but also excellent long term stability due to the inherent properties of quartz in combination with several enhancements implemented over the last few years. The total uncertainty of the 7250xi and 7250i over a one year calibration interval is 0.009% of reading down to 5% and 25%, respectively (see the table, above right). Simplified specifications eliminate guesswork and “specmanship” to allow you to determine the actual performance delivered with every instrument.

Standard precision

For applications that do not require the level of performance provided in the 7250xi or 7250i, the Model 7250 offers an economical approach to automatic pressure testing and calibration with a precision of 0.003% of full scale for ranges to 2 500 psi (17.2 MPa).

High pressure precision

For applications that require pressures up to 3 000 psi (21 MPa), the Model 7250HP provides total uncertainty (one year calibration interval) of 0.013% of reading down to 30% of the full scale. The 7250HP provides the high speed control and performance of the standard 7250 with a full scale pressure range of 3 000 psi (21 MPa) absolute.

High-speed pressure control

All Series 7250 instruments up to 2 500 psi (17.2 bar) reach setpoint in 20 seconds or less into a 15 cubic inch (245 cc) volume, with no overshoot, to allow high-speed pressure test and calibration.

Dual control modes

The Series 7250 also provides two user-selectable control modes: active and passive

mode. In active mode, the 7250 is continually maintaining the setpoint and can compensate for small leaks and pressure changes due to temperature. In passive mode, the user defines a control band and the 7250 will turn off the controller once it achieves the setpoint within the control band. In a leak-free and temperature-stable system, passive mode contributes no additional uncertainty, providing optimum performance.

Automating pressure test and calibration

The 7250xi, 7250i and 7250 are easy to use and can automate your calibrations in several ways:

Step up/down: for calibrations where the increments are fixed intervals, enter a user-defined step value. The Series 7250 increases or decreases the pressure by the step amount with the jog dial—no more lengthy keystroke sequences to program.

Sweep test: for simple exercising routines, as with dial gauges, enter a start value, a stop value, and number of times to repeat the cycle. The Series 7250 will automatically exercise the device under test prior to the calibration run.

Onboard programs: For frequently used or lengthy calibrations, the Series 7250 can store up to 20 user-defined programs/profiles with up to 1000 steps total in internal memory.

Computer interface: Every Series 7250 is provided with both an RS-232 and IEEE-488 interface, and Series 7250 syntax follows SCPI protocol for easy programming. COMPASS®, an off-the-shelf software package is available in addition to the LabVIEW® driver, a free download and optional MET/CAL® driver. As a standard feature, software written for the previous generation Series 7215, 7010 and 6000 instruments is fully supported by the Series 7250. The Series 7250 can also be set to 510 emulation mode to use software originally written for the DPI 510. Firmware updates can also be performed over the RS-232 interface.

Versatility to handle any pneumatic pressure calibration

The Series 7250 is versatile enough to handle almost any type of pneumatic pressure calibration.

Wide pressure range: available with any full scale pressure between 5 and 2 500 psi (35 kPa and 17.2 MPa) or for higher pressures select the 3 000 psi absolute (21 MPa) range.



The Series 7250 features a unique fused-quartz sensor. This rugged transducer offers unequalled precision and a stability of 0.0075% of reading per year.

Pressure units/scales: Select from over twelve standard units of measure, including inHg at 0 °C and 60 °F, kPa, bar, psi, inH₂O at 4 °C, 20 °C and 60 °F, kg/cm², mmHg at 0 °C, cmHg at 0 °C, and cmH₂O at 4 °C, and two user-defined units.

Head pressure: Automatic correction for head pressure differences

Absolute mode: The 7250i and 7250 offer three different methods to make absolute pressure measurements. The barometric reference option provides the most convenient method and is available on ranges 15 psi (1.0 bar) and higher. Alternatively, the vacuum reference option allows the connection of an external vacuum pump to the reference port of the instrument. An onboard vacuum sensor monitors the reference vacuum and allows for automatic zeroing in absolute mode. This option provides the lowest overall uncertainty since it does not include the additional uncertainty of a secondary barometric reference sensor. For pressure to 50 psia (350 kPa) permanent absolute models are also available. The 7250xi is only available with the barometric reference option for absolute measurement.

Autovent and autozero: With few keystrokes, the Series 7250 will vent the test port to atmosphere or automatically zero itself (autovent is not applicable to permanent absolute models).

Protection of the device under test: Set upper and lower pressure limits to ensure protection of the device under test.

Options


The Series 7250 can be provided for gauge mode operation, or with:

- Optional vacuum (negative gauge) mode for bidirectional devices
- Optional barometric reference for absolute mode calibrations
- Permanent absolute ranges to 50 psia (350 kPa) full scale which include a tare feature for simulated gauge mode operation

The Series 7250 Pressure Controller/Calibrator can easily automate your test and calibration workload. All are easy to use, easy to maintain, and have the reliability, performance and features that you want. The Series 7250 features an easy-to-navigate menu structure with full text descriptions for menus and commands.



The large color display allows the pressure value to be displayed even when viewing a submenu selection such as the units selection screen shown above.



All Series 7250s are fully programmable and can store up to 20 separate programs with up to 1000 steps.

Specifications

General	
Temperature	Operating: 18 °C to 36 °C (64 °F to 96 °F) Storage: -20 °C to 70 °C (-4 °F to 158 °F)
Humidity	5 % to 95 % RH, non-condensing
Weight	Model 7250/7250i: 7.7 kg (17 lb) Model 7250xi: 9 kg (20 lb)
Dimensions (H x W x D)	All versions: 178 mm x 419 mm x 483 mm (7 in x 16.5 in x 19 in)
Pressure medium	Nitrogen or clean dry air
Display	TFT, VGA, active matrix, 162.5 mm (6.4 in) 640 x 480 resolution, 65,000 colors
Test port and supply connection	1/4 in NPT female
Warm up time	2 to 3 hours; may be left on indefinitely
Pressure ranges	
Model 7250xi	Any Full Scale pressure range from 20 psig to 2 500 psig (140 kPa to 17.2 MPa).
Model 7250i	Any Full Scale pressure range from 5 psig to 2 500 psig (35 kPa to 17.2 MPa). Or, Permanent Absolute ranges from 15 psia to 50 psia (100 kPa to 350 kPa absolute).
Model 7250	Any Full Scale pressure range from 5 psig to 2 500 psig (35 kPa to 17.2 MPa). Or, Permanent Absolute ranges from 15 psia to 50 psia (100 kPa to 350 kPa absolute). For ranges below 35 kPa (5 psi), see the 7250LP.
Optional modes	Absolute using barometric reference sensor for ranges from 15 psig to 2 500 psig (100 kPa to 17.2 MPa)
	Vacuum (negative gauge)
	Vacuum reference (requires external vacuum pump)
Model 7250HP	3000 psi absolute (21 MPa absolute)
Performance	
Precision ¹	Model 7250xi: From 5 % to 100 % full scale (FS): 0.005 % of reading Below 5 % FS: 0.005% of 5% FS
	Model 7250i: From 25 % to 100 % FS: 0.005 % of reading Below 25 % FS: 0.005 % of 25 % FS
	Model 7250: Ranges to 2 500 psi (17.2 MPa): 0.003 % of FS
	Model 7250HP: 0.012% of reading or 0.0036% FS, whichever is greater
Stability	Ranges 2 500 psi (17.2 MPa): 0.0075 % of reading per year 3 000 psia (21 MPa) range: 0.005% of reading
Control stability	Active mode: 0.001 % FS (10 ppm) Passive mode: no additional uncertainty
Display resolution	User selectable to 1:1,000,000
Control response	20 seconds or less with zero overshoot into a 245 cm (15 in ³) volume for ranges to 2 500 psi (17.2 MPa) 60 seconds for 3 000 psia (21 MPa) range
Negative gauge precision (optional)	Model 7250xi: 0.005 % of 5 % FS or 0.00075 psi (0.05 mbar), whichever is greater
	Model 7250i: 0.005 % of 25 % FS or 0.0075 psi (0.5 mbar), whichever is greater
	Model 7250: 0.003 % of FS
	Model 7250HP: Not applicable
Barometric reference (optional)	0.002 psi (0.014 kPa) maximum error per year
Vacuum reference (optional)	0.0002 psi (0.0014 kPa) maximum error per year (Only available on 7250i and 7250)
Calibration	
An accredited calibration report is provided standard. For information on the calibration uncertainty, please see the appropriate Fluke Calibration Scope of Accreditation.	

Total Uncertainty (k=2) ²	
Model 7250xi	5 % to 100 % FS 90 day: 0.006 % reading 1 year: 0.009 % reading
Model 7250i	25 % to 100 % FS 90 day: 0.006 % reading 1 year: 0.009 % reading
Model 7250	90 day: 0.003 % FS + 0.002 % reading 1 year: 0.003 % FS + 0.0075 % reading
Model 7250HP	30 % to 100 % FS 90 day: 0.012 % reading 1 year: 0.013 % reading
Control parameters	
Volume	82 cm to 980 cm (5 in ³ to 60 in ³)
Low Control (absolute)	0.15 psia (1 kPa)
Communications	
RS-232 and IEEE-488, SCPI syntax. Series 7215, Model 7010, Series 6000 and DPI 510 emulation are standard.	
MET/CAL® driver	Optional
LabView® driver	Optional
Firmware updates are performed via RS-232 interface	
Languages	
The Series 7050 is capable of displaying menus and functions in: English, French, Chinese, German, Japanese, Spanish and Italian	
Options	
Barometric reference (absolute and vacuum) Vacuum mode (negative gauge) Vacuum reference (requires external vacuum pump)	
Accessories	
3911197	Transportation Case with Wheels and Handles
3879677	Rack mount kit for 19 in. EIA cabinets, 24 in. deep
3879689	Rack mount kit for 19 in. EIA cabinets, 30 in. deep
3876298	Lines and Fittings Kit
4014713	Vacuum Pump with auto-vent, 85 liters/minute
3876271	Liquid Trap
3891089	MET/CAL Pseudo-Driver
3070175	COMPASS for Pressure Enhanced, Single License
Model 7250i	Uncertainty (2 sigma)
Precision	0.005 % of reading
Stability (one year)	0.0075 % of reading
Calibration standard	0.0010 % of reading
Environmental temperature (included in precision)	0.000 % of reading
Head pressure	0.001 % of reading
Expanded uncertainty (2 sigma)	0.009 % of reading

¹ Precision is defined as the combined effects of linearity, repeatability and hysteresis throughout the operating temperature range.

² Total uncertainty is the maximum deviation from the true value of pressure including precision, stability, temperature effects and the calibration standard. This assumes routine zeroing of the instrument. Expression of uncertainty conforms with the recommendations of the ISO Guide to the Expression of Uncertainty in Measurement.

Fluke Calibration. Precision, performance, confidence.™

Electrical	RF	Temperature	Pressure	Flow	Software
------------	----	-------------	----------	------	----------

Fluke Calibration
PO Box 9090, Everett, WA 98206 U.S.A.

Fluke Europe B.V.
PO Box 1186, 5602 BD
Eindhoven, The Netherlands

For more information call:
In the U.S.A. (877) 355-3225 or
Fax (425) 446-5116
In Europe/M-East/Africa +31 (0) 40
2675 200 or Fax +31 (0) 40 2675 222
In Canada (800)-36-FLUKE or
Fax (905) 890-6866

From other countries +1 (425) 446-5500 or
Fax +1 (425) 446-5116
Web access: <http://www.flukecal.com>

©2010 Fluke Corporation.
Specifications subject to change without notice.
Printed in U.S.A. 9/2011 3833773B D-EN-N

Modification of this document is not permitted without written permission from Fluke Corporation.